

WISI DM 13 A

SAT splitter, 3-way



Description

The DM 13 A is a triple distributor which enables the symmetrical division of antenna signals on 3 lines. The integrated DC bypasses enable the pass-through of distributor voltage. The distribution attenuation is 10,5 dB. High shielding properties (class A) guarantee an interference-free transmission of the signals in the input and distribution systems.

At a glance:

- Frequency range from 5....2400 MHz
- Screening factor according to Class A
- DC-Bypass over every output
- High port isolation and return loss

WISI Communications GmbH & Co. KG

Wilhelm-Sihn-Str. 5-7
75223 Niefern - Oeschelbronn, Germany

Phone: +49 7233 66-280, Fax: -350
E-Mail: export@wisi.de

Technical Modifications reserved. WISI cannot be held liable for any printing error. 11. August 2017, 2:55 nachm.

Technical data

Frequency range	5...2400 MHz
Distribution loss	7...10,5 dB
Isolation	>20 dB
Return loss	18 dB

Connectors

F-socket	4 pcs. (1x input, 3x output)
----------	------------------------------

General data

Screening factor	>85 dB (class A)
DC Bypass IN/OUT 1A/30V	Yes
Dimensions (width x height x depth)	74x55x18 mm

Packaging data

Sales unit	1 pcs.
Dimensions (WxHxD) sales unit	370 x 320 x 170 mm
Packaging volume sales unit	dm ³
Gross weight sales unit	0.060 kg
Shipping unit	100 pcs.
Dimensions (WxHxD) shipping unit	mm
Packaging volume shipping package	0.2 dm ³
Gross weight shipping unit	0.06 kg
EAN	4010056165789
Article number	16578
Customs tariff number	85291095