

WISI DY 06

Multiswitch, stand alone & cascade



Description

EMV according to CE, class A; terr. input level max. 89 dB μ V;
with the 13V/18V, 22 KHz-control signal can max. 4 inputs be
controlled

At a glance:

- Active
- Kaskade & Stand Alone
- 9 inputs
- 6 participants outputs

WISI Communications GmbH & Co. KG

Wilhelm-Sihn-Str. 5-7
75223 Niefern - Oeschelbronn, Germany

Phone: +49 7233 66-280, Fax: -350
E-Mail: export@wisi.de

Technical Modifications reserved. WISI cannot be held liable for any printing error. 7. Juni 2016, 3:05 nachm.

Technical data

SAT-IF trunk

Inputs SAT	8 pcs.
Frequency range SAT	950...2400 MHz
Gain SAT	15 dB
Decoupling SAT -SAT	>27 dB
Output level SAT	111 dB (SAT 3. Ord. EN 50083-3/35dB)

Terrestrial trunk

Inputs TERR	1 pcs.
Frequency range TERR	5...862 MHz
Insertion loss TERR	6 dB
Subscriber outputs	6 pcs.
Frequency range	5...2400 MHz
Tap loss TERR	22 dB
Tap loss SAT	0 dB
Decoupling Subscriber - Subscriber TERR	>42 dB
Decoupling Subscriber - Subscriber SAT	>30 dB

Connectors

F-socket	24 pcs.
----------	---------

General data

Operating voltage AC	230 V
Operating voltage DC	14 V DC
Power input standby	<1,5 W
Power consumption	17,5/<4,5 W (with LNB/without LNB)
LNB supply voltage	14 V
LNB electrical power supply	0.7 A
Screening factor (EMC)	Class A, EN 50083-2
Dimensions (width x height x depth)	210x139x58 mm
casadable with	DY 94A...98A
Control signal	14/18V, 22 kHz, DiSEqC 2.0

Packaging data

Sales unit	1 pcs.
Dimensions (WxHxD) sales unit	207 x 140 x 64 mm
Packaging volume sales unit	dm ³
Gross weight sales unit	1.100 kg
Shipping unit	5 pcs.
Dimensions (WxHxD) shipping unit	mm
Packaging volume shipping package	1.85 dm ³
Gross weight shipping unit	1.1 kg
EAN	4010056139728
Article number	13972
Customs tariff number	85291095