

WISI DY 50 A

SAT amplifier



A
CLASS

Description

At a glance:

- 4 SAT-input/output + 1 TERR. input/output
- Input: 0...15 dB-Attenuator for SAT/TERR
- Return channel: 0...10 dB
- High shielding class A
- Stand-by function
- Return path- and ASTRA-IES-suitable

WISI Communications GmbH & Co. KG

Wilhelm-Sihn-Str. 5-7
75223 Niefern - Oeschelbronn, Germany

Phone: +49 7233 66-280, Fax: -350
E-Mail: export@wisi.de

Technical Modifications reserved. WISI cannot be held liable for any printing error. 7. Juni 2016, 3:05 nachm.

Technical data

terrestrial

Frequency range TERR	85...862 MHz
Gain TERR	15...22 dB
Output level 1	115 dB μ V (3.system EN50083-3, 60 dB)
Attenuator TERR	0...15 dB
Frequency range return channel	5...65 MHz
Gain return channel	8...9 dB
Attenuator return channel TERR	0...10 dB

SAT

Frequency range SAT	950...2400 MHz
Gain SAT	16...23 dB
Output level 2	115 dB μ V (3.order EN50083-3, 35 dB)
Noise figure SAT	11...4 dB
Attenuator SAT	0...15 dB
Isolation trunk	38 dB

Connectors

F-socket	12 pcs.
----------	---------

General data

Operating voltage DC	13/14 V DC
Current consumption 13/14 V DC	370 mA
Output voltage	13/14 V DC
Screening factor (EMC)	Class A, EN 50083-2
Dimensions (width x height x depth)	140x140x27 mm
Operating temperature range	0...+55 °C

Packaging data

Sales unit	1 pcs.
Dimensions (WxHxD) sales unit	197 x 230 x 75 mm
Packaging volume sales unit	dm ³
Gross weight sales unit	0.600 kg
Shipping unit	pcs.
Dimensions (WxHxD) shipping unit	mm
Packaging volume shipping package	3.4 dm ³
Gross weight shipping unit	0.6 kg
EAN	4010056141288
Article number	14128
Customs tariff number	85437030