

WISI DY 58 B

Multiswitch, stand alone & cascade



Description

EMV according to CE, Klasse A; terr. input level max. 70 dB μ V

At a glance:

- Kaskade & Stand Alone

Technical data

SAT-IF trunk

Inputs SAT	4 pcs.
Frequency range SAT	950...2400 MHz
Gain SAT	15 dB
Decoupling SAT -SAT	30 dB
Output level SAT	105 dB (SAT 3. Ord. EN 50083-3/35dB)

Terrestrial trunk

Inputs TERR	1 pcs.
Frequency range TERR	5...862 MHz
Gain TERR	14 dB
Output level TERR	105 dB μ V (TERR 3. Ord. EN 50083-3/60dB)
Subscriber outputs	pcs.
Frequency range	5...2400 MHz
Tap loss TERR	2 dB
Tap loss SAT	0 dB
Decoupling Subscriber - Subscriber TERR	>42 dB
Decoupling Subscriber - Subscriber SAT	>30 dB

Connectors

F-socket	16 pcs.
----------	---------

General data

Operating voltage AC	230 V (50/60 Hz)
Operating voltage DC	14 V DC
Power input standby	<1,5 W
Power consumption	17,5/<3,9 W (with LNB/without LNB)
LNB supply voltage	14 V
LNB electrical power supply	0.29 A
Screening factor (EMC)	Class A, EN 50083-2
Dimensions (width x height x depth)	139x139x58 mm
cascadable with	DY 44A...48A
Control signal	22 kHz (13/18 V)

Packaging data

Sales unit	1 pcs.
Dimensions (WxHxD) sales unit	207 x 140 x 64 mm
Packaging volume sales unit	dm ³
Gross weight sales unit	0.800 kg
Shipping unit	5 pcs.
Dimensions (WxHxD) shipping unit	mm
Packaging volume shipping package	1.85 dm ³
Gross weight shipping unit	0.8 kg
EAN	4010056136833
Article number	13683
Customs tariff number	85291095