

# WISI DY 94 A

Multiswitch, cascade



## Description

EMC according to CE, class A, terr. input level max. 89 dB $\mu$ V;  
With the 13V/18V, 22 KHz-control signal max. 4 inputs can be controlled.

## At a glance:

- passive
- Kaskade
- 9 inputs
- 4 participants outputs

## Technical data

SAT-IF trunk	
Inputs SAT	8 pcs.
Frequency range SAT	950...2400 MHz
Insertions loss SAT	1,3...3,4 dB
Decoupling SAT -SAT	27 dB

## Terrestrial trunk

Inputs TERR	1 pcs.
Frequency range TERR	5...862 MHz
Insertion loss TERR	5.5 dB
Subscriber outputs	4 pcs.
Frequency range	5...2400 MHz
Tap loss TERR	21 dB
Tap loss SAT	21...16 dB (5 dB slope)
Decoupling Subscriber - Subscriber TERR	>42 dB
Decoupling Subscriber - Subscriber SAT	>30 dB

## Connectors

F-socket	22 pcs.
----------	---------

## General data

Screening factor (EMC)	Class A, EN 50083-2
Dimensions (width x height x depth)	210x139x27 mm
cascadable with	DY 94A...98A, DY 04...08, DY 90
Control signal	14/18 V, 22 kHz, DiSEqC 2.0

## Packaging data

Sales unit	1 pcs.
Dimensions (WxHxD) sales unit	230 x 150 x 65 mm
Packaging volume sales unit	dm <sup>3</sup>
Gross weight sales unit	1.200 kg
Shipping unit	5 pcs.
Dimensions (WxHxD) shipping unit	mm
Packaging volume shipping package	2.24 dm <sup>3</sup>
Gross weight shipping unit	1.2 kg
EAN	4010056137731
Article number	13773
Customs tariff number	85291095