

# WISI DM 34 C

Two-way tap, 16 dB



## Description

Indoor mounting, screening factor class A, return path compatible

**WISI Communications GmbH & Co. KG**

Wilhelm-Sihn-Str. 5-7  
75223 Niefern-Oeschelbronn, Germany

Phone: +49 7233 66-280, Fax: -350  
E-Mail: [export@wisi.de](mailto:export@wisi.de)

Technical Modifications reserved. WISI cannot be held liable for any printing error. 7. Juni 2016, 3:05 nachm.

## Technical data

Frequency range	5...1000 MHz
Through loss	0,8...1,2 dB
Side loss	16 dB
Directional attenuation	$\geq 35/\geq 28$ dB (5...470/470...1000 MHz)
Decoupling	$\geq 34$ dB
Return loss	18...22 dB

## Connectors

F-socket	4 pcs. (1x input, 1x run through, 2x branch)
----------	--

## General data

Screening factor (EMC)	>85 dB (class A)
DC Bypass IN/OUT 1A/30V	no
Dimensions (width x height x depth)	78 x 50 x 27 mm

## Packaging data

Sales unit	10 pcs.
Dimensions (WxHxD) sales unit	370 x 320 x 170 mm
Packaging volume sales unit	dm <sup>3</sup>
Gross weight sales unit	0.062 kg
Shipping unit	100 pcs.
Dimensions (WxHxD) shipping unit	mm
Packaging volume shipping package	dm <sup>3</sup>
Gross weight shipping unit	0.062 kg
EAN	4010056703059
Article number	70305
Customs tariff number	85291095