

# WISI DM 51 1010

One-way tap, 11 dB



## Description

The DM 51 1010 is a single splitter for cable TV and satellite TV. The insertion loss is 2.5 dB and the tap loss is 11 dB. The integrated DC bypass enables the pass-through of distributor voltage to active components. High shielding properties (class A) guarantee an interference-free transmission of the signals in the input and distribution systems. A fast and safe connection is ensured through F-sockets.

## At a glance:

- Frequency range from 5....2400 MHz
- Screening factor according to Class A
- DC-Bypass in the trunk line
- High port isolation and return loss

## Technical data

Frequency range	5...2400 MHz
Through loss	1,5...2,5 dB
TAP loss	11 dB
Directional attenuation	32/25/22 dB (5...40/40...100/100...2400 MHz)
Return loss	18...22 dB

## Connectors

F-socket	3 pcs. (1x input, 1x run through, 1x branch)
----------	--

## General data

Screening factor	>85 dB (class A)
DC Bypass IN/OUT 1A/30V	Yes
Dimensions (width x height x depth)	52 x 50 x 18 mm

## Packaging data

Sales unit	1 pcs.
Dimensions (WxHxD) sales unit	36 x 32 x 19 mm
Packaging volume sales unit	dm <sup>3</sup>
Gross weight sales unit	0.060 kg
Shipping unit	200 pcs.
Dimensions (WxHxD) shipping unit	mm
Packaging volume shipping package	dm <sup>3</sup>
Gross weight shipping unit	0.06 kg
EAN	4010056165970
Article number	16597
Customs tariff number	85291095